

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

DUPLICATE

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A

PORTION OF THE NORTH BOUNDARY,

A PORTION OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES

AND

SUBDIVISION OF SECTIONS 5, 9, 10 AND 11

OF

TOWNSHIP 48 SOUTH, RANGE 33 EAST

OF THE

Of the Tallahassee Meridian,

In the State of Florida

EXECUTED BY

Anthony E. Carrow

Cadastral Surveyor

Under special instructions dated February 14, 1989, approved February 14, 1989

, which provided for the surveys included under U.S. Survey/Group
Number 186, and assignment instructions dated February 14, 1989.

Survey commenced March 9, 1989

Survey completed May 31, 1989

INDEX DIAGRAM

Township 48 South, Range 33 East,

4 2 6 12	3 12 8 11	3 10 4 10	3 8 8	6 2 5	1
2 7	11 8	9 9 9	6 10 6	5 11 5	4 12
13	17	16	15	5 14	13
19	20	21	22	23	24
20	20	26	27	26	25
31	32	33	34	35	36

SUBDIVISION OF SECTION 5	PG. 12
SUBDIVISION OF SECTION 9	PG. 12 - 14
SUBDIVISION OF SECTION 10	PG. 14 - 15
SUBDIVISION OF SECTION 11	PG. 15 - 18

Township 48 South, Range 33 East,
Tallahassee Meridian, Florida

CHAINS

The history of surveys of Township 48 South, Range 33 East, Tallahassee Meridian, Florida, is as follows:

The north boundary of the township was surveyed by Timothy S. Starns, Deputy Surveyor, in 1874, plat approved October 31, 1874.

The east, west and south boundaries, and the subdivisional lines were surveyed by Marcellus A. Williams, Deputy Surveyor, in 1875, plat approved October 9, 1875. The exterior boundaries and a portion of the subdivisional lines were dependently resurveyed by Lester S. Mann, Public Land Surveyor, in 1939, plat approved January 14, 1941. Portions of the north boundary and subdivisional lines were dependently resurveyed by Louis D. Gilbert, Cadastral Surveyor, in 1975, plat approved February 13, 1978.

The following field notes describe the dependent resurvey of a portion of the north boundary, a portion of the west boundary, a portion of the subdivisional lines and subdivision of sections 5, 9, 10 and 11 of Township 48 South, Range 33 East, Tallahassee Meridian, Florida.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated February 14, 1989, for Group No. 186, Florida.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of the lines were determined by hour angle observations of the sun, and refer to the true meridian. The lines were carried forward by sustained angulation, being supplemented by other observations taken throughout the progress of the survey.

The geographic position of the southeast corner of section 11, determined from a direct tie to U.S. Coast and Geodetic Survey triangulation station, "CORNER", 1970, located in section 12, Township 48 South, Range 34 East, Tallahassee Meridian, Florida, is as follows:

Latitude: 26°18'54.73" N. Longitude: 80°59'38.31" W.
"NAD 27"

The mean magnetic declination is 2° West.

Dependent Resurvey, Portion of W. Bdy.,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

(Restoring the survey executed by
Marcellus A. Williams in 1875 and the
Dependent Resurvey by Lester S. Mann, in 1939)

Beginning at the cor. of secs. 7, 12, 13, and 18, on
the W. bdy. of the Tp., monumented with a concrete post,

Dependent Resurvey, Portion of W. Bdy.,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS	
	<p>6 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the official record of the 1939 resurvey; from which the remains of the 1939 bearing trees:</p> <p>A cypress, 10 ins. diam., bears N. 68 1/4° E., 65 lks. dist., mkd. with healed blazes at breast height and at base.</p> <p>A cypress, 13 ins. diam., bears S. 62 1/2° E., 28 lks. dist., mkd. with a healed blaze at breast height.</p> <p>Cor. falls in a fence line extending N. and S.</p> <p>N. 1°57.0' W., bet. secs. 7 and 12, along a fence line.</p>
39.973	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; monumented by persons unknown, with a concrete post, 3 ins. sq., firmly set, projecting 35 ins. above the ground. There is no remaining evidence of the orig. cor. Not remonumented.</p> <p>Cor. falls in a fence line extending N. and S.</p>
79.946	<p>Point for the cor. of secs. 1, 6, 7 and 12; at proportionate dist.; monumented by persons unknown, with a concrete post, 3 ins. sq., firmly set, projecting 29 ins. above the ground. There is no remaining evidence of the 1939 cypress post. Not remonumented.</p> <p>From this cor., an iron pipe, 1 1/2 ins. diam., loosely set, projecting 14 ins. above the ground, with screw on cap, not mkd. bears S. 36°17.0' E., 0.034 chs. dist.</p> <p>Cor. falls 1 1/2 lks. E. of a fence line extending N. and S.</p>
39.973	<p>N. 1°57.0' W., bet. secs. 1 and 6, along a fence line.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist.; monumented by persons unknown, with a concrete post, 3 ins. sq., firmly set, projecting 6 ins. above the ground, mkd. with an "X" on top. There is no remaining evidence of the orig. cor. Not remonumented.</p> <p>Cor. falls 2 lks. E. of a fence line extending N. and S.</p>
79.946	<p>The cor. of Tps. 47 and 48 S., Rs. 32 and 33 E., monumented with a concrete post, 6 ins. diam., loosely set, projecting 14 ins. above the ground, with brass cap mkd. as described in the official record of the 1939 resurvey. There is no remaining evidence of the 1939 bearing trees.</p> <p>Cor. falls at the cor. of fences, extending N., E. and S.</p>
	<p>Dependent Resurvey, Portion of N. Bdy., T. 48 S., R. 33 E., Tallahassee Meridian, Florida</p> <p>(Restoring the survey executed by Timothy S. Starns, in 1874 and the Dependent Resurvey by Lester S. Mann, in 1939</p>

Dependent Resurvey, Portion of N. Bdy.,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS	
	<p>From the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with a concrete post, 6 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the official record of the 1939 resurvey. There is no remaining evidence of the 1939 witness post.</p> <p>Cor. falls in a fence line extending E. and W.</p> <p>S. 89°05.5' W., bet. secs. 3 and 34, along a fence line.</p>
40.491	<p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.</p>
80.982	<p>Point for the cor. of secs. 3, 4, 33 and 34 at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.</p>
	<hr/>
	<p>S. 89°05.5' W., bet. secs. 4 and 33, along a fence line.</p>
40.491	<p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.</p>
80.982	<p>The cor. of secs. 4, 5, 32 and 33, monumented with a concrete post, 6 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the official record of the 1939 resurvey; from which the remains of a 1939 bearing tree:</p> <p>A cabbage palm, 11 ins. diam., bears S. 32 1/2° W., 147 lks. dist., mkd. with an "X" at breast height.</p> <p>Cor. falls in a cor. of fence lines extending E., S. and W.</p>
	<hr/>
	<p>S. 89°05.4' W., bet. secs. 5 and 32, along a fence line.</p>
40.501	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; monumented by Prewitt and Associates, in 1960, with an iron pipe, 1 3/4 ins. diam., firmly set, projecting 12 ins. above the ground, with a screw-in cap, 2 ins. diam., not mkd.</p> <p>At the cor. point</p> <p>Set an aluminum sectional rod, 36 ins. long, 3/4 in. diam., driven 30 ins. in the ground, with the top 24 ins. encased in concrete, 4 ins. diam., with aluminum cap especially designed for the project mkd.</p> <p style="text-align: center;">T47S R33E 1/4 <u>S32</u> S5 T48S 1989</p> <p>There are no suitable bearing trees within limits.</p> <p>Deposit a bare magnet, 1 in. long, 7/8 in. diam., alongside aluminum sectional rod.</p> <p>Reset iron pipe alongside aluminum sectional rod.</p> <p>Cor. falls at the cor. of fence lines extending E., S. and W.</p>

Dependent Resurvey, Portion of N. Bdy.,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS	
81.002	<p>The cor. of secs. 5, 6, 31 and 32, monumented with a concrete post, 6 ins. diam., firmly set, projecting 20 ins. above the ground, with brass cap mkd. as described in the official record of the 1939 resurvey. There is no remaining evidence of the 1939 witness point.</p> <p>Cor. falls in a fence line extending E. and W.</p> <hr/> <p>S. 89°07.3' W., bet. secs. 6 and 31, along a fence line.</p>
40.517	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.</p>
82.381	<p>The cor. of Tps. 47 and 48 S., Rs. 32 and 33 E.</p> <hr/> <p>Dependent Resurvey, Portion of Subdivisional Lines, T. 48 S., R. 33 E., Tallahassee Meridian, Florida</p> <hr/> <p>(Restoring the survey executed by Marcellus A. Williams, in 1875, and the Dependent Resurvey by Lester S. Mann, in 1939, and the Dependent Resurvey by Louis D. Gilbert, in 1975)</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14, monumented with a concrete post, 6 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the official record of the 1975 resurvey.</p> <p>N. 1°47.9' W., bet. secs. 11 and 12.</p>
20.100	<p>Point for the S 1/16 sec. cor. of secs. 11 and 12; not monumented. There is no remaining evidence for the cypress post set in the 1939 resurvey.</p>
40.200	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd. as described in the official record of the 1975 resurvey.</p> <hr/> <p>N. 1°47.9' W., beginning new measurement.</p>
20.100	<p>There is no remaining evidence of the cypress post set in the 1939 resurvey.</p>
40.200	<p>The cor. of secs. 1, 2, 11 and 12, monumented with a concrete post, 6 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the official record of the 1975 resurvey.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23, monumented with a concrete post, 6 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the official record of the 1939 resurvey. There is no remaining evidence of the 1939 bearing trees.</p> <p>from which the new bearing trees:</p> <p>A cypress, 9 ins. diam., bears N. 13° E., 204 lks. dist., mkd. T48S R33E S14 BT and with aluminum tag attached.</p>

Dependent Resurvey, Portion of Subdivisional Lines,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS	
	<p>A cypress, 7 ins. diam., bears N. 86° E., 151 lks. dist., mkd. T48S R33E S14 BT and with aluminum tag attached.</p> <p>There is no other available bearing trees.</p> <p>Cor. falls at the projection of a fence line extending E.</p> <p>Cor. falls in an improved field, 12 lks. West of the W. bank of a canal, 6 ft. wide, bearing S. 27° E. and N. 27° W.</p> <p>N. 0°19.0' W., bet. secs. 14 and 15.</p>
40.166	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist., there is no remaining evidence of the orig. cor. Not monumented.
80.332	<p>Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; monumented by Armando L. Benavides, R.L.S. No. 2268 of Johnson-Prewitt & Associates, Inc. in 1979, with a concrete post, 4 ins. sq., firmly set, projecting 2 ins. above the ground, with aluminum cap, 3 ins. diam., mkd. "X". There is no remaining evidence of the orig. cor. Not remonumented.</p> <hr/> <p>N. 89°21.9' E., bet. secs. 11 and 14.</p>
40.508	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.
60.762	Point for the E 1/16 sec. cor. of secs. 11 and 14. Not monumented.
81.016	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 2°01.2' W., bet. secs. 10 and 11.</p>
40.190	Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.
80.380	<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist; there is no remaining evidence of the orig. cor. Not monumented.</p> <p>From this cor., a concrete post, 4 ins. sq., firmly set, flush with the ground, bears N. 89°56.8' E., 0.355 chs. dist., with aluminum cap, 3 ins. diam. mkd. "X".</p> <hr/> <p>N. 89°20.5' E., bet. secs. 2 and 11.</p>
40.658	Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.
81.316	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 0°59.9' W., bet. secs. 2 and 3.</p>

Dependent Resurvey, Portion of Subdivisional Lines,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS	
40.172	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.
80.484	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.
	<p>From the cor. of secs. 9, 10, 15 and 16, monumented with a concrete post, 6 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the official record of the 1939 resurvey; from which the remains of a 1939 bearing tree:</p> <p style="padding-left: 40px;">A cypress, 10 ins. diam., bears N. 51° W., 38 lks. dist., mkd. with a healed blaze at base.</p> <p>Cor. falls in a cor. of fence lines extending S. and W. N. 89°20.2' E., bet. secs. 10 and 15.</p>
40.256	Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.
80.512	The cor. of secs. 10, 11, 14 and 15.
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 2°17.4' W., bet. secs. 9 and 10.</p>
40.096	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set an aluminum sectional rod, 36 ins. long, 3/4 in. diam., driven 24 ins. in the ground, the top 24 ins. encased in concrete, 4 ins. diam., with aluminum cap especially designed for this project mkd.</p> <p style="text-align: center;">T48S R33E 1/4 S9 S10 1989</p> <p>from which</p> <p style="padding-left: 40px;">A cypress, 7 ins. diam., bears S. 37° E., 12 1/2 lks. dist., mkd. 1/4 S10 BT.</p> <p style="padding-left: 40px;">A cypress, 9 ins. diam., bears N. 61° W., 18 lks. dist., mkd. 1/4 S9 BT.</p> <p>Deposit a bare magnet, 1 in. long, 7/8 in. diam., alongside aluminum rod.</p> <p>Set a pvc pipe, 5 ft. long, 1 in. diam., driven 1 ft. in the ground, 1.0 ft. N. of cor.</p>
50.120	<p>Point for the S-N 1/64 sec. cor. of secs. 9 and 10.</p> <p>Set an aluminum sectional rod, 36 ins. long, 3/4 in. diam., driven 24 ins. in the ground, the top 24 ins. encased in concrete, 4 ins. diam., with aluminum cap especially designed for this project mkd.</p>

Dependent Resurvey, Portion of Subdivisional Lines,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS

S-N
1/64
S9|S10
1989

from which

A cypress, 9 ins. diam., bears S. 50° E., 36 lks.
dist., mkd. S-N 1/64 S10 BT.

A cypress, 8 ins. diam., bears N. 60° W., 3 lks.
dist., mkd. S-N 1/64 S9 BT.

Deposit a bare magnet, 1 in. long, 7/8 in. diam.,
alongside aluminum rod.

Set a pvc pipe, 5 ft. long, 1 in. diam., driven 1 ft.
in the ground, 1.0 ft. N. of cor.

60.144 Point for the N 1/16 sec. cor. of secs. 9 and 10. Not
monumented.

80.192 Point for the cor. of secs. 3, 4, 9 and 10, at
proportionate dist.; there is no remaining evidence of
the orig. cor.

Set an aluminum sectional rod, 36 ins. long, 3/4 in.
diam., driven 30 ins. in the ground, the top 24 ins.
encased in concrete, 4 ins. diam., with aluminum cap
especially designed for this project mkd.

T48S R33E
S4|S3
S9|S10
1989

from which

A cypress, 6 ins. diam., bears N. 88° E., 160 lks.
dist., mkd. T48S R33E S3 BT.

A cypress, 9 ins. diam., bears S. 86° E., 188 lks.
dist., mkd. T48S R33E S10 BT.

A cypress, 12 ins. diam., bears S. 80° W., 33 lks.
dist., mkd. T48S R33E S9 BT.

A cypress, 6 ins. diam., bears N. 11° W., 25 lks.
dist., mkd. T48S R33E S4 BT.

Deposit a bare magnet, 1 in. long, 7/8 in. diam.,
alongside aluminum rod.

Set a pvc pipe, 5 ft. long, 1 in. diam., driven 1 ft.
in the ground, 1.0 ft. N. of cor.

From this cor., an iron pipe, 2 ins. diam., firmly set,
projecting 2 ins. above the ground, bears
N. 75°56.8 E., 1.614 chs. dist.

From this same cor., a concrete post, 4 ins. sq.,
firmly set, projecting 6 ins. above the ground, bears
S. 70°03.2' E., 0.299 chs. dist.

N. 89°11.6' E., bet. secs. 3 and 10.

20.218 Point for the W 1/16 sec. cor. of secs. 3 and 10. Not
monumented.

Dependent Resurvey, Portion of Subdivisional Lines,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS		
40.436	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set an aluminum sectional rod, 36 ins. long, 3/4 in. diam., driven 36 ins. in the ground, the top 24 ins. encased in concrete, 4 ins. diam., with aluminum cap especially designed for this project mkd.</p> <p style="text-align: center;">T48S R33E 1/4 $\frac{S3}{S10}$ 1989</p> <p>from which</p> <p style="padding-left: 40px;">A cypress, 6 ins. diam., bears N. 57° E., 36 1/2 lks. dist., mkd. 1/4 S3 BT.</p> <p style="padding-left: 40px;">A cypress, 4 ins. diam., bears N. 25° W., 25 1/2 lks. dist., mkd. 1/4 S3 BT.</p> <p>There are no available bearing trees in sec. 10.</p> <p>Deposit a bare magnet, 1 in. long, 7/8 in. diam., alongside aluminum rod.</p> <p>Set a pvc pipe, 5 ft. long, 1 in. diam., driven 1 ft. in the ground, 1.0 ft. N. of cor. is cor., a fence line, extending E. and W., bears North, 20 1/2 lks. dist.</p> <p>From this same cor., the center line of a gravel road, 30 ft. wide, bearing E. and W., bears South, 63 1/2 lks. dist.</p>	
80.872	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>From the cor. of secs, 3, 4, 9 and 10.</p> <p>N. 1°05.0' W., bet. secs. 3 and 4.</p>	
40.070	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.</p>	
80.340	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17, monumented with a concrete post, 6 ins. diam., firmly set, 30 ins. below the surface, with brass cap mkd. as described in the official record of the 1939 resurvey; from which the remains of the 1939 bearing trees:</p> <p style="padding-left: 40px;">A cypress, 7 ins. diam., bears S. 33 1/2° E., 250 lks. dist.; chopped into face of tree to reveal a portion of the 1939 blaze mkd. "E S16 BT".</p> <p style="padding-left: 40px;">A cypress, 6 ins. diam., bears S. 75° W., 219 lks. dist.; chopped into face of tree to reveal a portion of the 1939 blaze mkd. "R 33E S17".</p> <p>Cor. falls 8 lks. East of the center line of a drainage ditch levee, 15 ft. wide, bearing N. and S.</p>	

Dependent Resurvey, Portion of Subdivisional Lines,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS	
	N. 89°14.0' E., bet. secs. 9 and 16.
20.400	There is no remaining evidence of the cypress post set in the 1939 resurvey.
40.795	The 1/4 sec. cor. of secs. 9 and 16, monumented with a concrete post, 6 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. as described in the official record of the 1939 resurvey; from which the remains of the 1939 bearing trees: <p>A decayed cypress stump, size indeterminate, bears S. 36° W., 10 lks. dist.</p> <p>A cypress, 6 ins. diam., bears N. 30 1/2° W., 5 lks. dist., mkd. with healed blaze.</p> <p>Cor. falls in old downed fence line, extending E. and W.</p> <p>N. 89°14.0' E., beginning new measurement.</p>
20.395	There is no remaining evidence of the cypress post set in the 1939 resurvey.
40.795	The cor. of secs. 9, 10, 15 and 16. <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 2°07.9' W., bet. secs. 8 and 9.</p>
40.066	Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.
60.099	Point for the N 1/16 sec. cor. of secs. 8 and 9. Not monumented.
80.132	Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor. <p>Set an aluminum sectional rod, 72 ins. long, 3/4 in. diam., driven 66 ins. in the ground, the top 24 ins. encased in concrete, 4 ins. diam., with aluminum cap especially designed for this project mkd.</p> <p>T48S R33E S5 S4 S8 S9 1989</p> <p>from which</p> <p>A live oak, 12 ins. diam., bears N. 73° E., 20 lks. dist., mkd. T48S R33E S4 BT.</p> <p>A powerpole, bears N. 23° W., 92 lks. dist., to a nail in base.</p> <p>No other available bearing trees.</p> <p>Deposit a bare magnet, 1 in. long, 7/8 in. diam., alongside aluminum rod.</p> <p>Set a pvc pipe, 5 ft. long, 1 in. diam., driven 1 ft. in the ground, 1.0 ft. N. of cor.</p>

Dependent Resurvey, Portion of Subdivisional Lines,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS	
	<p>Cor. falls on top of a drainage ditch levee, 15 ft. wide, bearing E. and W.</p> <p>From this cor., a concrete post, 3 1/2 ins. sq., firmly set, projecting 12 ins. above the ground, bears N. 84°38.9' E., 0.919 chs. dist., with 1 in. diam. brass cap in center mkd. "T48 R33 4 5 8 9 R.P." with "X" in the center. The concrete post is at the cor. of fence lines extending N., E., S. and W.</p>
	<p>N. 89°12.1' E., bet. secs. 4 and 9.</p>
20.337	<p>Point for the W 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set an aluminum sectional rod, 36 ins. long, 3/4 in. diam., driven 36 ins. in the ground, the top 24 ins. encased in concrete, 4 ins. diam., with aluminum cap especially designed for this project mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S4}{S9}$ 1989</p> <p>There are no available bearing trees.</p> <p>Deposit a bare magnet, 1 in. long, 7/8 in. diam., alongside aluminum rod.</p> <p>Set a pvc pipe, 5 ft. long, 1 in. diam., driven 1 ft. in the ground, 1.0 ft. N. of cor.</p> <p>From this cor., the center line of a gravel road, 30 ft. wide, bearing N. 58° E. and S. 58° W., bears West, 1.450 chs. dist.</p>
40.674	<p>Point for the 1/4 sec. cor. of secs. 4 and 9 at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.</p>
81.348	<p>The cor. of secs. 3, 4, 9 and 10.</p>
	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 0°49.7' W., bet. secs. 4 and 5.</p>
40.042	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.</p>
80.184	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.</p>
	<p>From the cor. of secs. 7, 8, 17 and 18, monumented with the remains of the 1939 concrete post, 36 ins. long, 6 ins. diam. The top 12 ins. of the concrete, along with the brass cap, were broken away and are missing. The 1 in. iron pipe at the center was bent over at a 45° angle to the W. and found flush with ground surface. The base of the post was still intact. There is no remaining evidence of the 1939 bearing trees.</p> <p>At the cor. point</p> <p>Set an aluminum sectional rod, 36 ins. long, 3/4 in. diam., driven 36 ins. in the ground, the top 24 ins.</p>

Dependent Resurvey, Portion of Subdivisional Lines,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS

encased in concrete, 4 ins. diam., with aluminum cap especially designed for this project mkd.

T48S R33E
S7|S8
S18|S17
1989

There are no available bearing trees.

Deposit a bare magnet, 1 in. long, 7/8 in. diam., alongside aluminum rod.

Set a pvc pipe, 5 ft. long, 1 in. diam., driven 2 ft. in the ground, 1.0 ft. N. of cor.

Dispose of the remains of the 1939 concrete post.

Cor. falls in a citrus plantation, 23 lks. North of the N. bank of a drainage ditch, 15 ft. wide, bearing S. 50° E. and N. 50° W.

N. 1°56.9' W., bet. secs. 7 and 8.

40.031 Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.

80.062 Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.

From this cor., a concrete post, 3 1/2 ins. sq., broken off at ground level, with 18 ins. lying on the ground, bears N. 85°33.2' E., 0.902 chs. dist., with 1 in. diam. brass cap in center, mkd. "5 6 7 8" and "X" in the center.

N. 89°08.1' E., bet. secs. 5 and 8.

40.620 Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.

Set an aluminum sectional rod, 36 ins. long, 3/4 in. diam., driven 32 ins. in the ground, the top 24 ins. encased in concrete, 4 ins. diam., with aluminum cap especially designed for this project mkd.

T48S R33E
1/4 S5
S8
1989

There are no available bearing trees.

Deposit a bare magnet, 1 in. long, 7/8 in. diam., alongside aluminum rod.

Set a pvc pipe, 5 ft. long, 1 in. diam., driven 1 ft. in the ground, 1.0 ft. N. of cor.

From this cor., an iron pipe, 1 3/4 ins. diam., firmly set, projecting 12 ins. above the ground, with a screw on cap, 2 ins. diam., not mkd., bears N. 86°08.4' E., 0.915 chs. dist. This iron pipe is at the cor. of fence lines extending E. and N.

Dependent Resurvey, Portion of Subdivisional Lines,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS	
81.240	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>From the cor. of secs 5, 6, 7 and 8.</p> <p>S. 89°15.4' W., bet. secs. 6 and 7.</p>
40.568	<p>Point for the 1/4 sec. cor. of secs. 6 and 7 at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.</p>
80.599	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°39.9' W., bet. secs. 5 and 6.</p>
40.010	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.</p>
80.120	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.</p> <hr/> <p>Subdivision of Section 5, T. 48 S., R. 33 E., Tallahassee Meridian, Florida</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. 0°44.8' W., on the N. and S. center line of the sec. 5.</p>
80.153	<p>The 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp.</p> <hr/> <p>Subdivision of Section 9, T. 48 S., R. 33 E., Tallahassee Meridian, Florida</p> <hr/> <p>From the 1/4 cor. of secs. 9 and 16.</p> <p>N. 2°12.4' W., on the N. and S. center line of sec. 9.</p>
40.088	<p>Point for the C 1/4 sec. cor. of sec. 9, at the intersection with the E. and W. center line of sec. 9.</p> <p>Set an aluminum sectional rod, 48 ins. long, 3/4 in. diam., driven 44 ins. in the ground, the top 24 ins. encased in concrete, 4 ins. diam., with aluminum cap especially designed for this project mkd.</p> <p style="text-align: center;">T48S R33E C 1/4 S9 1989</p> <p>from which</p> <p>A live oak, 16 1/2 ins. diam., bears N. 29° E., 60 1/2 lks. dist., mkd. C 1/4 BT.</p> <p>A cypress, 6 1/2 ins. diam., bears S. 18° W., 67 lks. dist., mkd. C 1/4 BT.</p>

Subdivision of Section 9,
T. 48 S., R. 33 E., Tallahassee Meridian, Florid

CHAINS	
	<p>Deposit a bare magnet, 1 in. long, 7/8 in. diam., alongside aluminum rod.</p> <p>Set a pvc pipe, 5 ft. long, 1 in. diam., driven 1 1/2 ft. in the ground, 1.0 ft. N. of cor.</p>
60.127	<p>Point for the C-N 1/16 sec. cor. of sec. 9.</p> <p>Set an aluminum sectional rod, 18 ins. long, 3/4 in. diam., driven 6 ins. into solid rock, the top 12 ins. encased in concrete, 4 ins. diam., with aluminum cap especially designed for this project mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16\ S9 \\ C \\ 1989 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A cypress, 6 ins. diam., bears N. 86° E., 23 lks. dist., mkd. CN 1/16 BT.</p> <p style="padding-left: 40px;">A cypress, 7 ins. diam., bears N. 74° W., 31 lks. dist., mkd. CN 1/16 BT.</p> <p>Deposit a bare magnet, 1 in long, 7/8 in. diam., alongside aluminum rod.</p> <p>Set a pvc pipe, 5 ft. long, 1 in. diam., driven 1 ft. in the ground, 1.0 ft. N. of cor.</p>
80.166	<p>The 1/4 sec. cor. of secs. 4 and 9.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>S. 89°13.2' W., on the E. and W. center line of sec. 9.</p>
40.736	<p>The C 1/4 sec. cor. of sec. 9</p>
61.102	<p>Point for the C-W 1/16 sec. cor. of sec. 9. Not monumented.</p>
81.468	<p>The 1/4 sec. cor. of secs. 8 and 9.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 9.</p> <p>N. 2°10.2' W., on the N. and S. center line of the NW 1/4 of sec. 9.</p>
20.036	<p>Point for the NW 1/16 sec. cor. of sec. 9, at the intersection with the E. and W. center line of the NW 1/4 of sec. 9.</p> <p>Set an aluminum sectional rod, 24 ins. long, 3/4 in. diam., driven 18 ins. into the ground to solid rock, the top 18 ins. encased in concrete, 4 ins. diam., with aluminum cap especially designed for this project mkd.</p> <div style="text-align: center;"> $\begin{array}{c} NW\ 1/16\ S9 \\ 1989 \end{array}$ </div> <p>There are no available bearing trees.</p> <p>Deposit a bare magnet, 1 in. long, 7/8 in. diam., alongside aluminum rod.</p>

Subdivision of Section 9,
T. 48 S., R. 33 E., Tallahassee Meridian, Florid

CHAINS	
	Set a pvc pipe, 5 ft. long, 1 in. diam., driven 1 ft. in the ground, 1.0 ft. N. of cor.
40.072	The W 1/16 sec. cor. of secs. 4 and 9.
	From the C-N 1/16 sec. cor. of sec. 9.
	S. 89°12.6' W., on the E. and W. center line of the NW 1/4 of sec. 9.
20.352	The NW 1/16 sec. cor. of sec. 9.
40.704	The N 1/16 sec. cor. of secs. 8 and 9.
	Subdivision of Section 10, T. 48 S., R. 33 E., Tallahassee Meridian, Florida
	From the 1/4 sec. cor. of secs. 10 and 15.
	N. 2°09.3' W., on the N. and S. center line of sec. 10.
40.144	Point for the C 1/4 sec. cor. of sec. 10, at the intersection with the E. and W. center line of sec. 10. Not monumented.
50.179	Point for the C-S-N 1/64 sec. cor. of sec. 10.
	Set an aluminum sectional rod, 36 ins. long, 3/4 in. diam., driven 34 ins. in the ground, the top 24 ins. encased in concrete, 4 ins. diam., with aluminum cap especially designed for this project mkd.
	<div>C S-N 1/64 S10 C 1989</div>
	There are no available bearing trees.
	Deposit a bare magnet, 1 in. long, 7/8 in. diam., alongside aluminum rod.
	Set pvc pipe, 5 ft. long 1 in. diam., driven 1 ft. in the ground, 1.0 ft. N. of cor.
60.214	Point for the C-N 1/16 sec. cor. of sec. 10. Not monumented.
80.284	The 1/4 sec. cor. of secs. 3 and 10.
	From the 1/4 sec. cor. of secs. 10 and 11.
	S. 89°15.9' W., on the E. and W. center line of sec. 10.
40.346	The C 1/4 sec. cor. of sec. 10.
60.519	Point for the C-W 1/16 sec. cor. of sec. 10. Not monumented.
80.692	The 1/4 sec. cor. of secs. 9 and 10.
	From the C-W 1/16 sec. cor. of sec. 10.

Subdivision of Section 10,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS

	N. 2°13.3' W., on the N. and S. center line of the NW 1/4 of sec. 10.
10.029	Point for the C-S-NW 1/64 sec. cor. of sec. 10. Not monumented.
20.058	Point for the NW 1/16 sec. cor. of sec. 10, at the intersection with E. and W. center line of the NW 1/4 of sec. 10. Not monumented.
49.117	The W 1/16 sec. cor. of secs. 3 and 10.
	From the C-N 1/16 sec. cor. of sec. 10.
	S. 89°13.7' W., on the E. and W. center line of the NW 1/4 of sec. 10.
20.196	The NW 1/16 sec. cor. of sec. 10.
40.392	The N 1/16 sec. cor. of secs. 9 and 10.
	From the C-S-N 1/64 sec. cor. of sec. 10.
	S. 89°14.8' W., on the E. and W. center line of the SE 1/4 of the NW 1/4 of sec. 10.
20.184	The S-N 1/64 sec. cor. of secs. 9 and 10.
	S. 89°14.8' W., on the E. and W. center line of the SW 1/4 of the NW 1/4 of sec. 10.
20.184	The S-N 1/64 sec. cor. of secs. 9 and 10.
Subdivision of Section 11, T. 48 S., R. 33 E., Tallahassee Meridian, Florida	
	From the 1/4 sec. cor. of secs. 11 and 14.
	N. 1°54.4' W., on the N. and S. center line of sec. 11.
20.098	Point for the C-S 1/16 sec. cor. of sec. 11. Not monumented.
40.196	Point for the C 1/4 sec. cor. of sec. 11, at the intersection with E. and W. center line of sec. 11. Not monumented.
80.394	The 1/4 sec. cor. of secs. 11 and 12.
	From the 1/4 sec. cor. of secs. 11 and 12.
	S. 89°21.4' W., on the E. and W. center line of sec. 11.
10.143	Point for the E-E 1/64 sec. cor. of sec. 11. Not monumented.
20.286	Point for the C-E 1/16 sec. cor. of sec. 11. Not monumented.
40.572	The C 1/4 sec. cor. of sec. 11.
81.155	The 1/4 sec. cor. of secs. 10 and 11.

Subdivision of Section 11,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS	
	<p>From the E 1/16 of secs. 11 and 14.</p> <p>N. 1°51.7' W., on the N. and S. center line of the SE 1/4 of sec. 11.</p>
20.099	Point for the SE 1/4 sec. cor. of sec. 11, at the intersection with the E. and W. center line of the SE 1/4 of sec. 9. Not monumented.
25.124	<p>Point for the C-S-N-SE 1/256 sec. cor. of sec. 11.</p> <p>Set an aluminum sectional rod, 36 ins. long, 3/4 in diam., driven 36 ins. in the ground, the top 12 ins. encased in concrete, 6 ins. diam., with aluminum cap especially designed for this project mkd.</p> <p style="text-align: center;">S11 C-S-N-SE 1/256 1989</p> <p>No bearing trees were taken.</p> <p>Deposit a bare magnet, 1 in. long, 7/8 in. diam., alongside aluminum rod.</p> <p>From this cor., an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, bears S. 81°08.3' E., 0.034 chs. dist.</p>
30.144	From this point, an iron rod, 5/8 in. diam., firmly set, 2 ins. below the ground surface, bears East, 0.033 chs. dist.
35.174	<p>Point for the C-N-N-SE 1/256 sec. cor. of sec. 11.</p> <p>Set an aluminum sectional rod, 36 ins. long, 3/4 in. diam., driven 36 ins. in the ground, the top 12 ins. encased in concrete, 6 ins. diam., with aluminum cap especially designed for this project mkd.</p> <p style="text-align: center;">S11 C-N-N-SE 1/256 1989</p> <p>No bearing trees were taken.</p> <p>Deposit a bare magnet, 1 in. long, 7/8 in. diam., alongside aluminum rod.</p> <p>From this cor., an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, bears S. 84°48.4' E., 0.041 chs. dist.</p>
40.199	<p>The C-E 1/16 sec. cor. of sec. 11.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>S. 89°21.7' W., on the E. and W. center line of the SE 1/4 of sec. 11.</p>
20.270	The SE 1/16 sec. cor. of sec. 11.
40.540	<p>The C-S 1/16 sec. cor. of sec. 11.</p> <hr/> <p>From the C-S-N-SE 1/256 sec. cor. of sec. 11.</p>

Subdivision of Section 11,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

CHAINS	
	N. 89°21.7' E., on the E. and W. center line of the SW 1/4 of the NE 1/4 of the SE 1/4 of sec. 11.
10.137	<p>Point for the C-S-NE-SE 1/256 sec. cor. of sec. 11.</p> <p>Set an aluminum sectional rod, 54 ins. long, 3/4 in. diam., driven 54 ins. in the ground, the top 12 ins. encased in concrete, 6 ins. diam., with aluminum cap especially designed for this project mkd.</p> <p>S11 C-S-NE-SE 1/256 1989</p> <p>No bearing trees were taken.</p> <p>Deposit a bare magnet, 1 in. long, 7/8 in. diam., alongside aluminum rod.</p> <p>From this cor., an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, bears N. 83°53.8' E., 0.019 chs. dist.</p>
	<hr/>
	N. 1°50.2' W. on the N. and S. center line of the NE 1/4 of the SE 1/4 of sec. 11.
5.029	From this point, an iron rod, 5/8 in. diam., firmly set, flush with the ground, bears East, 0.020 chs. dist.
8.028	<p>Point for angle point No. 1 at the intersection with the W. right-of-way (100 ft.) of State Road No. 833.</p> <p>Set an aluminum sectional rod, 24 ins. long, 1/2 in. diam., 24 ins. in the ground, with an aluminum cap mkd.</p> <p>SIR AP1 S11 1989</p> <p>from which</p> <p>A palm, 12 ins. diam., bears N. 60° E., 177 1/2 lks. dist., mkd. with a nail at base.</p> <p>A power pole, bears S. 1° E., 87 lks. dist., mkd. with a BT tag and a nail at base.</p> <p>From this cor., an iron rod, 5/8 in. diam., buried 4 ins. below the ground, bears N. 0°38.8' W., 0.428 chs.</p> <p>Thence along the W. right-of-way of State Road No. 833 on the arc of a circular curve to the right with a radius of 1956.53 ft., a central angle of 33°03'37" and a cord bearing and dist. of N. 42°13.3' W., 2.702 chs.</p>
2.703	<p>Point for angle point No. 2, at the intersection with the E. and W. center line of the NW 1/4 of the NE 1/4 of the SE 1/4 of sec. 11.</p> <p>Set an aluminum rod, 48 ins. long, 1/2 in. diam., 48 ins. in the ground, with aluminum cap mkd.</p> <p>SIR AP2 S11 1989</p>

Subdivision of Section 11,
T. 48 S., R. 33 E., Tallahassee Meridian, Florida

	CHAINS	<p>from which</p> <p>A pine, 15 ins. diam., bears S. 32° W., 15 1/2 lks. dist., mkd. BT at base and breast height.</p> <p>An oak, 6 ins. diam., bears N. 43° W., 109 lks. dist., mkd. BT at base and breast height.</p> <p>From this cor., an iron rod, 5/8 in. diam., buried 3 ins. below the ground, bears N. 89°17.0' E., 0.389 chs. dist.</p> <hr/> <p>S. 89°21.5' W., on the E. and W. center line of the NW 1/4 of the NE 1/4 of the SE 1/4 of sec. 11.</p> <p>8.390 The C-N-N-SE 1/256 sec. cor. of sec. 11.</p> <hr/> <p><u>General Description</u></p> <p>The land encompassed in this survey is located about 33 miles south of Clewiston and 50 miles west of Ft. Lauderdale, Florida.</p> <p>Major access to the area is gained by Florida Highway No. S-833 which runs through the eastern portion of the township, and by various gravel roads which criss-cross the surveyed area.</p> <p>The area is generally flat with timber, consisting of pine, cabbage, palm and oak, with an undergrowth of palmetto and native grasses. There are packets of cypress swamps scattered throughout the surveyed area.</p> <p>There are houses scattered throughout the surveyed area, occupied by the Seminole Indians.</p> <p>The primary uses of the surveyed area are for housing developement, pasture land for grazing and the recent developement of large tracts of citrus plantations.</p>	
--	--------	--	--

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

[illegible]

48

CERTIFICATE OF SURVEY

(I) ~~was~~ Anthony E. Carrow

, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the **14th** day of **February**, 19 **89**, (I) ~~was~~ have **dependently resurveyed** a portion of the north boundary, a portion of the west boundary, a portion of the subdivisional lines and subdivision of sections 5, 9, 10 and 11 of Township 48 South, Range 33 East,

of the **Tallahassee** Meridian, in the State of **Florida**, which are represented in the foregoing field notes as having been executed by (me), ~~was~~ and under (my) ~~was~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 20, 1990

(Date)

/s/ Anthony E. Carrow

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Alexandria, Virginia

The foregoing field notes of the **dependent resurvey of a portion of the north boundary, a portion of the west boundary, a portion of the subdivisional lines and subdivision of sections 5, 9, 10 and 11 of Township 48 South, Range 33 East, Tallahassee Meridian, Florida,**

executed by **Anthony E. Carrow, Cadastral Surveyor,**

having been critically examined and found correct, are hereby approved.

June 8, 1990

(Date)

/s/ Stephen G. Kopach

(Signature of Authorized Officer)

(Chief Cadastral Surveyor, Eastern States Office)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in T. 48 S., R. 33 E., Tall. Mer., FL., is a true copy of the original field notes.

June 8, 1990

(Date)

Stephen G. Kopach
(Signature of Authorized Officer)

(Chief Cadastral Surveyor, Eastern States Office)